

LIGHT COLLECTING AND FOCUSING DEVICE

Cross Reference to Related Applications

[0001] This application claims the benefit of U.S. Provisional Patent Applications 60/307,565, filed on July 23, 2001; and 60/307,566, filed on July 23, 2001.

Field of the Invention

[0002] The present invention generally relates to the field of optics, and more specifically to a device for collecting, redirecting, and focusing optical energy.

Background

[0003] Ultrasonic pen digitizer systems continue to grow in both popularity and importance. Typically, ultrasonic pen or stylus digitizer systems utilize an ultrasonic transducer and optical transmitters, such as an infrared light emitting diodes (LEDs), attached to a stylus. Such a system is described in U.S. Patent Number 4,814,552, which is hereby incorporated by reference in its entirety. The optical transmitters, which are attached to the stylus, transmit optical signals, which are received almost instantaneously by an optical receiver (such as a photodiode). The ultrasonic transducer mounted to the stylus transmits acoustic pulses, which are received, with a delay as compared to receipt of the optical signal, by two (or more) receiver transducers positioned at fixed locations with respect to one another and having a specified separation therebetween. The position of the transducer and stylus is determined by triangulation from the measured time of the received signals from each of the receivers.

[0004] The optical receiver is mounted to a receiving portion of the system (not the stylus) such that it is in the line of sight of at least one of the LEDs

mounted on the stylus. As a user "writes" with the stylus, it is not uncommon for the stylus to rotate. To ensure that the optical receiver is always in the line of sight of the optical transmitters, typical digitizing systems mount three LEDs to the stylus equidistantly positioned on a perimeter of the stylus tip. This configuration
5 of the optical transmitters ensures that the optical receiver and at least one of the LEDs are in a line of sight with each other as the stylus tip is rotated.

[0005] Because of the plurality of LEDs required to maintain line of sight coupling, such a system dissipates a relatively large amount of power, requires electronic circuitry for each LED, and results in a relatively short battery life. A
10 digitizer system, which reduces power consumption and reduces circuit complexity is desired.

Summary Of The Invention

[0006] A device includes an optically conductive tip for redirecting an optical signal. The optically conductive tip is in direct line of sight of either the
15 optical transmitter(s) or the optical receiver(s). The device also includes an optical conductor, which is optically coupled to the tip. The optical conductor is in direct line of sight of the other of the optical transmitter(s) or optical receiver(s).

[0007] Another aspect of the invention is an apparatus comprising a housing having a longitudinal axis. A first optical device is positioned within the housing.
20 An optically conductive tip is mounted to the housing. An axis of the tip is coaxial with the axis of said housing. The tip is in direct line of sight of a second optical device. An optical conductor optically couples the first optical device to the tip. The first and second optical devices are optically coupled to each other by way of the tip and the optical conductor, regardless of an orientation of the
25 housing about its longitudinal axis.

[0008] Another aspect of the invention is a system for determining the position of a stylus. The system comprises a fixed transceiving portion for transceiving ultrasonic and optical signals. The fixed transceiving portion comprises at least one ultrasonic transducer, and at least one optical receiver or at least one optical transmitter. The stylus comprises an ultrasonic transducer and one of the group consisting of a single optical transmitter and a single optical receiver. A position of the stylus is determined in accordance with the optical signals and propagation times of the ultrasonic signals.

Brief Description Of The Drawings

10 [0009] The above and other advantages and features of the present invention will be better understood from the following detailed description of the preferred embodiments of the invention, which are provided in connection with the accompanying drawings. The various features of the drawings may not be to scale. Included in the drawing are the following figures:

15 [0010] Figure 1 is a perspective view of a digitizer system in accordance with a first embodiment of the present invention;

[0011] Figure 2 is an illustration of a portion of the stylus of FIG. 1;

[0012] Figure 3 is an exploded view of the stylus of FIG. 1;

20 [0013] Figure 4 is a perspective view of a digitizer system according an alternative embodiment of the present invention wherein the fixed transceiving portion comprises at least one optical transmitter and the stylus comprises an optical receiver; and

[0014] Figure 5 is an illustration of a portion of the stylus of FIG. 4, wherein the stylus comprises an optical receiver.

Detailed Description

[0015] U.S. Provisional Patent Applications 60/307,565, filed on July 23, 2001; and 60/307,566, filed on July 23, 2001 are incorporated by reference in their entireties, as though set forth fully herein.

5 [0016] Figure 1 is a perspective view of a digitizer system 100. Digitizer system 100 comprises a fixed transceiving portion 112 communicatively coupled with a portable transceiving portion (e.g., pen or stylus) 116. As used herein, a transceiver has the capability to transmit, receive, or both transmit and receive signals. Fixed transceiving portion 112 comprises a first ultrasonic transducer 118
10 fixed at a first position on a side surface of housing unit 122. Housing 122 preferably contains the electronic circuitry 124 for operation of the fixed transceiving system 112 and associated interconnections. Integration of the electronic circuitry 124 within the housing 122 may be accomplished in conventional fashion. A second ultrasound transducer 120 is fixed at a second
15 position on the side surface of unit 112 such that the distance between the two transducers (118 and 120) is known. At least one optical detector 114, such as a photodetector or photodiode, is also positioned on the side surface of unit 112 for detecting optical signals. Electronic circuitry 124 is coupled to transducers 118, 120 and optical detector 114, and operates to process the electronic signals
20 corresponding to the ultrasonic and optical signals utilized by the system 100 to perform timing measurements and triangulation calculations to determine the position of the stylus 116. In alternative embodiments, fixed transceiving portion 112 may be incorporated into a processor system, such as a personal computer and a video display device (e.g., a monitor).

25 [0017] Portable transceiving portion 116 comprises an ultrasonic transducer 126 mounted onto a movable pen or stylus 116 and operative as a receiver and/or transmitter (i.e., transceiver) for receiving and/or transmitting ultrasonic signals

from and/or to transceiving portion 112. An optical transmitter 128 is disposed on the stylus for transmitting optical signals to the fixed transceiving portion 112 to be received by optical receiver 114. Optical transmitter 128 is positioned within the stylus 116, and is hidden in Figure 1. System 100 further comprises a light
5 collecting and focusing device, tip 130, mounted to the stylus 116, and an optical conductor 222 (shown in Figure 2) positioned within stylus 116, between the optical transmitter 128 and the tip 130.

[0018] In FIG. 1, the exemplary optical transmitter 128 comprises a single optical transmitter, such as a light-emitting diode (LED) or other such
10 photoemitter mounted on the stylus 116 for transmitting optical signals through the optical conductor to the light collecting and focusing device 130 to the optical receiver 114 of fixed transceiver portion 112. Optical communication between the optical transmitter 128 and the at least one optical receiver 114 is maintained regardless of the orientation (see arrow 134) of the stylus 116 about its axis (see
15 arrow 132).

[0019] As is known in the art of digitizers and ultrasonic positioning devices, the difference between the propagation time from one of the fixed ultrasonic transducers (such as ultrasonic transducer 118) to the stylus 116 and the propagation time from the other fixed ultrasonic transducer (such as ultrasonic
20 transducer 120) to the same stylus is used to determine the position of the stylus. Also, as described in U.S. Patent Number 4,814,552, optical signals are utilized to provide and receive timing and data information. Conventional digitizing systems, however, utilize a plurality of optical transmitters on the stylus to ensure that the optical signal is "seen" (i.e., in direct line of sight) by the optical receiver.

25 [0020] In exemplary stylus 116, optical coupling between the optical transmitter 128 and the optical receiver 114 is maintained, regardless of the orientation of the stylus 116 about its axis, using only a single optical transmitting

device 128. Briefly, optical signals provided by optical transmitter 128 are optically coupled to tip 130 by an optical conductor 222 and an optically conductive channel 212 (shown in Figure 2). The tip 130 redirects the optical signal such that the redirected optical signal is in direct line of sight with the optical receiver 114, regardless of the orientation of stylus 116 about its axis 132.

[0021] Figure 2 shows a portion of the stylus 116. Stylus 116 comprises light collecting and focusing tip 130, optical conductor (light pipe) 222, ultrasonic transducer 126, protective grid 214, optical channel 212, and electrical conductors 218. Not shown in Figure 2 is a flexible printed circuit board (PCB), which is electrically coupled to electrical conductors 218 and positioned within stylus 116, when stylus 116 is completely assembled, such that optical channel 212 is optically aligned with optical transmitter 128. Also, when stylus 116 is completely assembled, the housing 224 of stylus 116 completely encloses the PCB, however, only a portion of the housing 224 is shown for the sake of clarity.

[0022] In some embodiments, ultrasonic transducer 126 comprises Polyvinylidene Fluoride (PVDF), a polymer piezoelectric material, formed into a film, wherein the film is wrapped around a cylindrical member positioned within stylus 116. Such an ultrasonic transducer is described in U.S. Patent Number 6,239,535, which is hereby incorporated by reference in its entirety. Various configurations of stylus 116 are envisioned. Descriptions of exemplary assembly configurations describing the coupling of the ultrasonic transducer to the cylindrical member, the coupling of the ultrasonic transducer to the electrical conductors, and the coupling of the electrical conductors to the flexible printed circuit board, are disclosed in provisional application numbers 60/307,565 and 60/307,566, incorporated by reference herein.

[0023] Arrows 220 indicate the direction and propagation paths of the optical signals provided by the optical transmitter 128. The optical signals (e.g.,

infrared signals, visible light) as provided by optical transmitter 128, are aligned with the optically conductive channel 212 at location 219. These optical signals propagate through the optically conductive channel 212 within the stylus 116, to light pipe 222 and tip 130. The optical signals are redirected by the tip 130 to
5 propagate approximately omnidirectionally, so that the optical signals can be received by the optical receiver 114 (see Figure 1). The axis of tip 130 is coaxial with the axis 132 of the stylus 116. Thus, the propagated optical signals are received by optical receiver 114, regardless of the orientation 134 of stylus 116 about its axis 132.

10 **[0024]** Figure 3 is an exploded view of stylus 116. In its assembled configuration, stylus 116 comprises light pipe 222 positioned within protection grid 214 and within ultrasonic transducer 126 (which may be a piezo film ultrasonic transmitter). The light pipe 222 is optically coupled to optically conductive channel 212 to funnel optical energy between the light pipe 222 and
15 the optical transmitter 128. Optical channel 212 is formed within stylus 116. Optical channel 212 may comprise any appropriate optically conductive channel, such as an optical waveguide, an optical fiber, or air. Optical channel 212 may be achromatic, in that the channel is optically transparent to all wavelengths of light. In another embodiment, optical channel 222 is transparent to infrared energy, and
20 may not necessarily be achromatic. In an alternative embodiment, light pipe 222 is optically coupled directly to the optical transmitter 128. This direct coupling may comprise any of several mechanisms, such as light pipe 222 being positioned in physical contact with the optical transmitter 128, or light pipe 222 being fused, welded, or adhesively coupled to optical transmitter 128.

25 **[0025]** Light collecting and focusing tip 130 may comprise any optically conductive material, such as polycarbonate. In alternative embodiments, the optically conductive material may be achromatic, or limited to being optically conductive to infrared energy. Light pipe 222 may also comprise any optically

conductive material, such as polycarbonate, and in alternative embodiments, the optically conductive material may be achromatic, or limited to being optically conductive to infrared energy.

[0026] Various embodiments of light pipe 222 and tip 130 are envisioned.

5 In a first embodiment, light pipe 222 and tip 130 are integrally formed from a single piece of material, such as polycarbonate, for example. For example, tip 130 and light pipe 222 may be formed from a single mold of polycarbonate or other appropriate material. In another embodiment, light pipe 222 and tip 130 are separate pieces of material. Thus, light pipe 222 and tip 130 may be formed by
10 separate molds of polycarbonate or other appropriate materials. Further, when the light pipe 222 and the tip 130 are formed as separate pieces, a portion of light pipe 222 may be inserted into the tip 130 as shown in Figures 2 and 3, or the light pipe 222 may not be inserted into tip 130 but rather may be coupled to the circular shaped base 131 of conical (or frustum) shaped tip 130. Light pipe 222 and tip
15 130 may be coupled by any appropriate means, such as welded, fused, adhesively coupled with an optically transparent adhesive, or positioned in close proximity to each other.

[0027] Figures 4 and 5 are illustrations of a system and stylus, respectively, wherein the positions of the optical transmitter 128' and optical receiver 114' are
20 interchanged. Figure 4, is a perspective view of a digitizer system 400 wherein the fixed transceiving portion 112' comprises at least one optical transmitter 128' and the stylus 116' comprises an optical receiver 114'. Digitizing system 400 functions in a similar manner to system 100, however optical signals are provided by optical transmitter 128' positioned on fixed transceiving portion 112', and the optical
25 signals are received by the optical receiver 114' positioned within stylus 116'.

[0028] Figure 5 shows a portion of the stylus 116 of FIG. 4, wherein the stylus comprises an optical receiver 114'. Arrows 520 indicate the direction and

propagation paths of the optical signals provided by the optical transmitter 128' on fixed transceiving portion 112'. The optical signals (e.g., infrared signals, visible light) as provided by optical transmitter 128', propagate through tip 130' to light pipe 222', through an optically conductive channel 212' within the stylus 116', to the optical receiver 114'. Location 219' of the optically conductive channel 212', is aligned with the optical receiver 114' to provide optical coupling such that conductive channel 212' is in optical communication with optical receiver 114'. The optical signals can be received by tip 130' from approximately all directions as shown by arrows 520. The omnidirectionally received optical signals are redirected by the tip 130' to propagate to light pipe 222' through optical channel 212', to the optical receiver 114' mounted on the printed circuit board.

[0029] In yet another embodiment of the invention, light pipe 222 may be optically coupled directly to the optical receiver 114. This direct coupling may comprise any of several mechanisms, such as light pipe 222 being positioned in physical contact with the optical receiver 114, or light pipe 222 being fused, welded, or adhesively coupled to optical receiver 114.

[0030] With only a single optical transmitter or single optical receiver mounted within the portable transceiving portion (e.g., stylus) of the exemplary systems 100 and 400, optical communication can be maintained between at least one optical transmitter and at least one optical receiver, regardless of the orientation of the stylus 116 about its axis. This allows a reduction in circuitry, weight and power consumption.

[0031] Many other variations are contemplated. For example, the number of ultrasonic transducers (e.g., 118, 120) on fixed transceiving portion 112 may be more or less than two. Also, the number of optical receivers 114 on fixed transceiving portion 112 (as in system 100), may be more than one, and the

number of optical transmitters 128 on fixed transceiving portion 112 (as in system 400), may also be more than one.

[0032] Although the invention is described in terms of exemplary embodiments, it is not limited thereto. Rather, the appended claims should be construed broadly, to include other variants and embodiments of the invention, which may be made by those skilled in the art without departing from the scope and range of equivalents of the invention. For example, tip 130 may be formed in a shape other than a frustum or a cone, such as a semispheroid, a semiparaboloid, or a semiellipsoid.

100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000